IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of)
Lars THYLÉN et al.)) Group Art Unit: Unassigned
Application No.: Unassigned)) Examiner: Unassigned
Filed: February 12, 2002))
For: A/D Conversion Method and Apparatus)))

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

Before examination, please amend this application as follows

IN THE ABSTRACT

Please replace the **ABSTRACT** with the following Abstract attached as a separate sheet:

100 · 100 · 100

Abstract

An opto-electronic A/D converter includes a tunable laser for wavelength modulating a narrowband coherent electromagnetic beam by the amplitude of the analog signal. A grating transforms the wavelength modulated beam into a corresponding angularly modulated beam. A set of kinoforms diffract the angularly modulated beam into a bundle of diffracted beams. Detectors determine the digital signal by repeatedly sampling the spatial power distribution of the diffracted beams.

41 MI

REMARKS

The Abstract has been amended to place the application in better form for examination. Favorable consideration is respectfully solicited.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

Theodosios Thomas Registration No. 45,159

P.O. Box 1404 Alexandria, Virginia 22313-1404 (919) 941-9240

Date: February 12, 2002

"Express Mail" mailing 'abel No EU74610+68SUS

2/12/02 Date of Deposit ..

I hereby certify that this panet or fee is being deposited with the United States Postal Service "Express Mail Post Office to I doressee" service under 37 CFR 1 10 on the data indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

(Type or printed name of person mailing paper or fee)

érs)n mailing paper or fee)

Attachment to Preliminary Amendment dated February 12, 2002

Marked Up Copy of Amendments to the Abstract

An opto-electronic A/D converter includes a tunable laser [(10)] for wavelength modulating a narrowband coherent electromagnetic beam by the amplitude of the analog signal. A grating [(12)] transforms the wavelength modulated beam into a corresponding angularly modulated beam. A set of kinoforms [(14)] diffract the angularly modulated beam into a bundle of diffracted beams. Detectors [(18, 20)] determine the digital signal by repeatedly sampling the spatial power distribution of the diffracted beams.